

Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **BUILDMASTER BM10**

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

#### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: BUILDMASTERUK LIMITED

Street/POB-No.: Unit 2, The Old Colliery Yard, Main Road, Morton, Alfreton,

State/postal code/city: Derbyshire DE55 6HL Telephone: +44 1773 475405

Contact point: BUILDMASTERUK LIMITED

Street/POB-No.: Unit 2, The Old Colliery Yard, Main Road, Morton, Alfreton,

Postal code/city:
Country:
United Kingdom
Telephone:

Derbyshire DE55 6HL
United Kingdom
+44 1773 475405

Information about the Safety Data Sheet: Telephone +44 1773 475405

eMail sales@buildmasteruk.com

**Emergency telephone number** 

Emergency Information: +44 1773 475405

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, Trimethoxyvinylsilane. May produce an allergic reaction. EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 **BUILDMASTER BM10** 

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

## n.a. **3.2 Mixtures**

N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	01-2119970215-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	217-164-6
CAS	1760-24-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Eye Dam. 1, H318
factors	Skin Sens. 1B, H317
	STOT SE 3, H335
Specific Concentration Limits and ATE	ATE (as inhalation, Vapours): 12,6 mg/l/4h

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 3, H226
factors	Acute Tox. 4, H332
	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Upon contact with stomach acid development of:

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes



Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Skin irritation possible with prolonged contact.

Developement of:

Methanol

The following applies to this substance:

Product results in a poisonous effect.

Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

#### Unsuitable extinguishing media

None known

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Methanol

Formaldehyde

Toxic gases

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

Flush residue using copious water.

#### 6.4 Reference to other sections



Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well ventilated place.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The methanol listed below can arise upon	contact with water.	
Chemical Name Silica,	amorphous	Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,	4 mg/m3   WEL-STEL:	
(resp. dust)		
Monitoring procedures:		
BMGV:	0	ther information:

N-(3-(trimethoxysilyl)propyl)ethylenediamine									
Area of application	Exposure route / Environmental	Effect on health	Descripto r	Value	Unit	Note			
	compartment								
	Environment - freshwater		PNEC	0,062	mg/l				
	Environment - marine		PNEC	0,0062	mg/l				
	Environment - water, sporadic (intermittent) release		PNEC	0,62	mg/l				
	Environment - sediment, freshwater		PNEC	0,05	mg/kg wet weight				
	Environment - sediment, marine		PNEC	0,005	mg/kg wet weight				
	Environment - sewage treatment plant		PNEC	25	mg/l				
	Environment - soil		PNEC	0,009	mg/kg				
Consumer	Human - oral	Long term, systemic effects	DNEL	2,5	mg/kg				
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m3				



Page 5 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Consumer	Human - inhalation	Long term, local effects	DNEL	0,1	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	2,5	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	35,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	5,36	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprech endes Silantriol (Hydrolys rodukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entsprech endes Silantriol (Hydrolys rodukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprech endes Silantriol (Hydrolys rodukt) ermittelt.
	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprech endes Silantriol (Hydrolys rodukt) ermittelt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprech endes Silantriol (Hydrolys rodukt) ermittelt.



Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprech endes Silantriol (Hydrolysp rodukt) ermittelt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprech endes Silantriol (Hydrolysp rodukt) ermittelt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	

Silica, amorphous										
Area of application	oplication Exposure route / Environmental compartment		Descripto r	Value	Unit	Note				
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3					

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). I WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). I BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) I Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.



Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Rubber gloves (EN ISO 374).

Protective gloves made of butyl (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Paste, solid.

Colour: According to specification

Odour: Characteristic



Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

Lower explosion limit:Does not apply to solids.Upper explosion limit:Does not apply to solids.Flash point:Does not apply to solids.Auto-ignition temperature:Does not apply to solids.

Does not apply to solids.

Decomposition temperature:

There is no information available on this parameter.

pH: Mixture is non-soluble (in water).

Kinematic viscosity: Does not apply to solids.

Solubility: Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,05 g/cm3

Relative vapour density:

Does not apply to solids.

9.2 Other information

Explosives: Product is not explosive.

Oxidizing solids:

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Strong heat

Protect from humidity.

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

#### 10.6 Hazardous decomposition products

See also section 5.2

On contact with moist air:

Methanol

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

BuildMaster BM10						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.



Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Specific target organ toxicity -				n.d.a.
single exposure (STOT-SE):				
Specific target organ toxicity -				n.d.a.
repeated exposure (STOT-				
RE):				
Aspiration hazard:				n.d.a.
Symptoms:		·		n.d.a.

N-(3-(trimethoxysilyl)propyl)						1
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2413	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	1,49-2,44	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Dam. 1
damage/irritation:					Eye	_, -,
damago/irriadiori.					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Skin Sens. 1B
sensitisation:				Guiriea pig	Sensitisation)	Skill Sells. 1D
				Marras	OECD 429 (Skin	Claim Comp. 1D
Respiratory or skin				Mouse		Skin Sens. 1B
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	Chinese
					Mutation Test)	hamster
Germ cell mutagenicity:				Mouse	OECD 474	Negative
-					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	
Reproductive toxicity	NOAEL	>=500	mg/kg	Rat	OECD 422	
(Developmental toxicity):	1107122		gg		(Combined Repeated	
(Bevelopmental toxioity).					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Demonstration to district /F#t-	NOAEL	. 500		D-4		
Reproductive toxicity (Effects	NOAEL	>=500	mg/kg	Rat	OECD 422	
on fertility):					(Combined Repeated	
					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Specific target organ toxicity -	NOAEL	>= 500	mg/kg	Rat	OECD 422	
repeated exposure (STOT-					(Combined Repeated	
RE), oral:					Dose Tox. Study with	
•					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Specific target organ toxicity -	NOAEC	0,015	mg/l/6h/d	Rat	OECD 413	
repeated exposure (STOT-	INOALO	0,013	mg///on/u	i iai		
					(Subchronic Inhalation	
RE), inhalat.:					Toxicity - 90-Day	
	1	1	1		Study)	I



Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Trimethoxyvinylsilane				1	1	T
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute	
oute:	1050	100	7/41	<b>.</b>	Dermal Toxicity)	.,
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute	Vapours
A	1.050	0770		D-4	Inhalation Toxicity)	A I
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute	Aerosol
Skin corrosion/irritation:				Rabbit	Inhalation Toxicity) OECD 404 (Acute	Not irritant
Skiii Coirosion/iiritation.				Паррії	Dermal	NOT IIIItalit
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:				Tiabbit	Eye	Not iiiitaiit
damago/imation.					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Skin Sens. 1B
sensitisation:				Guillou pig	Sensitisation)	Citiii Cono. 12
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
cona.a.gornon, .					Mammalian Cell Gene	Chinese
					Mutation Test)	hamster
Germ cell mutagenicity:		1		Mouse	OECD 474	Negative
					(Mammalian	3
					Èrythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo	Negative
					Mammalian Alkaline	_
					Comet Assay)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422	Negative
					(Combined Repeated	
					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
D	NOAE	7.5		D. I.I.	Test)	N1 1:
Reproductive toxicity	NOAEL	>= 75	mg/kg	Rabbit	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental	
Specific target organ toxicity -	LOAEL	0,58	ma/l	Rat	Toxicity Study) OECD 413	Vapours
repeated exposure (STOT-	LOAEL	0,56	mg/l	nai	(Subchronic Inhalation	vapours
RE), inhalat.:					Toxicity - 90-Day	
11L), IIII alat					Study)	
Symptoms:					Study)	drowsiness,
symptome.						dizziness,
						nausea,
						abdominal
						pain, breathin
						difficulties,
		1				visual
						disturbances
Specific target organ toxicity -	NOAEL	62,5	mg/kg	Rat	OECD 422	Target
repeated exposure (STOT-					(Combined Repeated	organ(s):
RE), oral:		1			Dose Tox. Study with	bladder
					the	
		1			Reproduction/Develop	
					m. Tox. Screening	
	İ	1		1	Test)	I



Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	Grai Toxioley)	References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizisir
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddene

#### 11.2. Information on other hazards

BuildMaster BM10									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Endocrine disrupting						Does not apply			
properties:						to mixtures.			
Other information:						No other			
						relevant			
						information			
						available on			
						adverse effects			
						on health.			

### **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

BuildMaster BM10								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to algae:							n.d.a.	
12.2. Persistence and							n.d.a.	
degradability:								
12.3. Bioaccumulative							n.d.a.	
potential:								
12.4. Mobility in soil:							n.d.a.	
12.5. Results of PBT							n.d.a.	
and vPvB assessment								
12.6. Endocrine							Does not apply	
disrupting properties:							to mixtures.	



Page 12 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

12.7. Other adverse	No information
effects:	available on
	other adverse
	effects on the
	environment.
Other information:	DOC-
	elimination
	degree(complex
	ing organic ing
	substance)>=
	80%/28d: n.a.
Other information:	Does not
	contain any
	organically
	bound
	halogens which
	can contribute
	to the AOX
	value in waste
	water.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.4. Mobility in soil:	•				, and the second		Slight
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	V
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	3,1	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	DOC	28d	39	%	activated sludge	Regulation (EC) 440/2008 C.4-A (DETERMINATI ON OF 'READY' BIODEGRADABI LITY - DOC DIE- AWAY TEST)	Not readily biodegradable
12.3. Bioaccumulative potential:							Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	25	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other organisms:	NOEC/NOEL	14d	>= 1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	



Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus	OECD 203	
•					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC)	
daphnia:						440/2008 C.2	
						(DAPHNIA SP.	
						ACUTE	
						IMMOBILISATIO	
						N TEST)	
12.1. Toxicity to	NOEC/NOEL	21d	28	mg/l	Daphnia magna	OECD 211	
daphnia:						(Daphnia magna	
						Reproduction	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum	OECD 201	
					capricornutum	(Alga, Growth	
				<del>                                     </del>		Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	25	mg/l	Selenastrum		
100 D	DOD	00.1		101	capricornutum	0E0D 004 E	N
12.2. Persistence and	BOD	28d	51	%		OECD 301 F	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Kow		1,1			1651)	Not to be
potential:	Log Now		1,1				expected 20 °C
QSAR							CAPCUICU ZU C
12.4. Mobility in soil:				+			Slight
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209	- Oligini
. comony to buotonia		•	- 2000	····g/·	don't allow old ago	(Activated	
						Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB
							substance
Toxicity to bacteria:	EC10	5h	1000	mg/l	Pseudomonas		
	1	1	1	1	putida		

Silica, amorphous								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203		
						(Fish, Acute		
						Toxicity Test)		
12.1. Toxicity to	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202		
daphnia:						(Daphnia sp.		
						Acute		
						Immobilisation		
						Test)		
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201		
						(Alga, Growth		
						Inhibition Test)		
12.2. Persistence and							Abiotically	
degradability:							degradable.	



Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

12.3. Bioaccumulative		Not to be
potential:		expected
12.4. Mobility in soil:		Not to be
		expected
12.5. Results of PBT		No PBT
and vPvB assessment		substance, No
		vPvB substance

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards:

Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments



Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

0 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

15

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHÁ Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately



Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw drv weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, E $\mu$ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential
Koc Adsorption coefficient of orga

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration



Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 19.01.2023

First Issue

PDF print date: 19.01.2023 BUILDMASTER BM10

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight